



KBS KLEAN

TDS/DIRECTIONS & APPLICATION INFORMATION



KBS Klean is a highly concentrated, water-based, multi-purpose, heavy-duty cleaner/degreaser. KBS Klean easily cleans and degreases in a single application leaving no residues, noxious odors, or flammable solvents. KBS Klean prepares your paint job with a clean and residue-free surface. Dirt, grime, oils, lubricants, grease, waxes, scum, mildew, road film, and other contaminants are effectively removed. KBS Klean is ideal for various household, industrial, commercial, and automotive applications. KBS Klean low-suds formula can be diluted up to 10 times its volume.

KBS KLEAN DEEPLY PENETRATES AND REMOVES SOIL AND STUBBORN STAINS FROM THE FOLLOWING SURFACES:

steel • iron • fiberglass • concrete • plastics
painted finishes • galvanized • aluminum
stainless steel • canvas • vinyl • nylon • brass

APPLICATIONS & USES INCLUDE:

pre-paint, pre-plate or pre-bond cleaning, automotive & diesel engines, machinery parts, car frames, heavy construction equipment, truck trailers, compressors, holding tanks, engine room pumping equipment, air conditioner systems, grease traps, floor pans, fuel tanks, transmissions, lawn mowers, tools, ovens, bbq grills, porcelain sinks, tubs, toilets and more.

KBS KLEAN SHOULD ALWAYS BE DILUTED WITH WATER.

NOTE: KBS Klean has a powerful low temp cleaning action but to improve efficiency & cleaning and obtain optimal results, use hot water. Effective dilution rates will vary according to the type and degree of contaminants as well as surface materials.

RECOMMENDED WATER DILUTION RATIOS:

Heavily Soiled Surfaces (Diesel engines, fuel tanks)
1 Part KBS Klean & 1 Part Hot Water

Moderately Soiled Surfaces (Pre-paint cleaning)
1 Part KBS Klean & 5 Parts Hot Water

Lightly Soiled Surfaces (Truck road film)
1 Part KBS Klean & 10 Parts Hot Water

PROTECTIVE RUBBER GLOVES AND SAFETY GLASSES SHOULD BE WORN AT ALL TIMES WHEN USING THIS PRODUCT.

DIRECTIONS:

Shake Well before each use. Dilute with water as recommended using a spray bottle if convenient. For general purpose cleaning, apply liberally and scrub surface for 5-10 minutes. Allow sufficient time for product to loosen or dissolve deposits. For heavy-duty cleaning, extended soaking times up to 24 hours or more may be necessary. Use a bristle brush or scouring pad to expedite the cleaning of heavily soiled surfaces. Retreat surface as necessary until clean. KBS Klean may also be used in power washing equipment to produce the rapid penetration of many layers of accumulated build up.

DO NOT ALLOW KBS Klean TO DRY before rinsing. Rinse thoroughly with water after cleaning and let dry. If rinsing is not possible, wipe treated surface with clean wet sponge or cloth to rinse well.

NOTE: For non-ferrous metals (aluminum, copper, brass, etc.), clean with KBS Klean at a dilution rate of 25 parts hot water to 1 part KBS Klean (4% strength) with the use of a very soft non-abrasive cleaning pad. Wipe the surface and so not soak. Rinse the KBS Klean solution immediately making sure you do not let it sit on the surface and dry in a way that minimizes any water stains.



PLEASE SEE SDS AND FOLLOW ALL WARNING AND CAUTIONS.

Made in the USA.

Information contained herein is to our knowledge true and accurate, but all recommendations or suggestions are made with out guarantee. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

KBS SUPPORT FORUM

SUCCESS.KBS-COATINGS.COM

COMPLETE How-To's

KBS-COATINGS.COM

KBS ONLINE INSTRUCTIONAL VIDEOS

VIEW 3-STEP SYSTEM APPLICATION VIDEOS
AVAILABLE ON KBS-COATINGS.COM

Revised 02/17/2026

CALL 219-263-0073

TEXT 219-531-7797

SUPPORT@KBS-COATINGS.COM

KBS-COATINGS.COM