



# KBS RUST CONVERTER

## DIRECTIONS & APPLICATION INFORMATION/TDS



***KBS Rust Converter easily converts a rusty surface into a black, inert primed surface that is ready for paint and compatible with most topcoats and also protects against future rust.***

***While the most permanent solution for rust prevention is the KBS 3-Step System of KBS Klean, RustBlast and RustSeal, KBS Rust Converter can be used when you are unable to use the KBS 3-Step System.***

To achieve expert results, please take the time to carefully read and understand the following directions before you begin your restoration project. If you have any remaining questions or concerns, please call us for technical assistance.

***ALWAYS WORK IN A WELL-VENTILATED AREA. A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS RECOMMENDED. ALWAYS WEAR PROTECTIVE GLOVES AND EYEWEAR.***

### **THEORETICAL COVERAGE:**

KBS Rust Converter Aerosol should convert and coat up to 20 sq. ft.

### **SURFACE PREP:**

***NOTE: THE SURFACE MUST BE RUSTY.***

KBS Rust Converter is not designed to use on any non-rusty surfaces or surfaces where you have a mix of rusty areas and non-rusty areas.

Use a wire brush or sandpaper to remove as much loose and flaky rust as possible. If needed, clean the surface with KBS Klean (10 Parts Hot Water & 1 Part KBS Klean).

### **APPLICATION:**

For best results, apply when can is between 50°-90°F.

***ALWAYS WEAR PROTECTIVE GLOVES AND EYE WEAR when using KBS Rust Converter. Always use NIOSH/MSHA approved air supplied respirator.***

Shake can well at least one minute after rattle is heard and occasionally during use.

Spray surface with steady even strokes at a distance of 8 to 12 inches. A chemical reaction will cause the rust to turn black.

Allow 24 hours before applying a second coat or when topcoating with a different coating.

If clogging develops, turn sprayhead ¼ turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.

### **CLEAN UP:**

KBS # 1 Thinner is ideal for clean up. Always wear protective gloves to avoid skin contact and temporary staining.

Please remember these instructions are general guidelines only and do not cover every application and environment. If you remain unsure as how to proceed, refer to product instruction sheet, our website: **KBS-Coatings.com**, or call for technical advice at **219-263-0073**.

**Please see SDS and follow all warning and cautions.**

## Made in the USA.

*Information contained herein is to our knowledge true and accurate, but all recommendations or suggestions are made without guarantee. Since application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.*



### **KBS SUPPORT FORUM**

**SUCCESS.KBS-COATINGS.COM**

### **COMPLETE How-To's**

**KBS-COATINGS.COM**

### **KBS ONLINE INSTRUCTIONAL VIDEOS**

**VIEW 3-STEP SYSTEM APPLICATION VIDEOS  
AVAILABLE ON KBS-COATINGS.COM**

Revised 04/17/2024

**1-219-263-0073**

**KBS-COATINGS.COM**